E-RAD **BLU-S**

Supreme Transducer Technology with High Accuracy.

The E-RAD BLU-S is the newest addition to the E-RAD BLU product line from RAD. Equipped with a transducer, the E-RAD BLU-S allows for the highest accuracy on the market and features operator identification, which ensures traceability of each torque sequence performed. With a pass/fail indicator on both sides, and password protection, you'll be sure you're getting controlled and accurate torquing.




E-RAD BLU TOUCH CONTROL CASE

The touch screen control case provides an easy to use interface that allows for preselectable presets, quick error-free torque and angle adjustments, complete recalibrations as well as data logging everything for easy export into spreadsheets on your laptop.

RAD SMART SOCKETS[™] can connect to the E-RAD BLU tool via Bluetooth technology. This combination allows you to automatically calibrate your E-RAD BLU to any joint!





| PART NUMBER | TOOL MODEL | DRIVE SIZE | TORQUI LOW | E (ft. lbs.) HIGH | RPM | WEIGHT (lbs.) | DIMENSION A | DIMENSION B | DIMENSION C | DIMENSION D |
|----------------|-----------------------|---------------|---------------|----------------------|-----|------------------|----------------|----------------|----------------|----------------|
| 30079 | E-RAD BLU 700-S | 0.75″ | 100 | 700 | 15 | 13 | 14.96″ | 2.84″ | 3.03″ | 10.65″ |
| 28836 | E-RAD BLU 2500-S COMP | 1.0″ | 250 | 2500 | 5 | 19 | 16.21″ | 3.41″ | 3.03″ | 10.65″ |
| 31190 | E-RAD BLU 3000-S | 1.0″ | 500 | 3000 | 5 | 24.5 | 17.76″ | 3.73″ | 3.48″ | 11.29″ |
| 31191 | E-RAD BLU 6000-S | 1.5″ | 1000 | 6000 | 2.1 | 30 | 17.71″ | 4.35″ | 3.48″ | 11.29″ |
| 31192 | E-RAD BLU 7500-S | 1.5″ | 1500 | 8000 | 1.5 | 34 | 18.53″ | 4.48″ | 3.48″ | 11.29″ |
| 29314 | E-RAD BLU 11K-S | 1.5″ | 3000 | 11,000 | 1.5 | 44 | 19.81″ | 5.21″ | 3.48″ | 11.29″ |