B-RAD S

The highest accuracy on the market.

The newest addition to the B-RAD series is the B-RAD S. Equipped with a built-in transducer, the B-RAD S makes torquing and logging easier and more efficient than ever with its ability to read and display torque in real time. With torque and angle capabilities, the B-RAD S is ready for the most critical applications and will hold up to scrutiny on a variety of projects. The B-RAD S includes Bluetooth connectivity, torque check functionality, and automatic reaction arm release to minimize your downtime and maximize your torque output.

- Torque range up to 7,000 Nm
- New and improved battery life
- Bolt counter
- Brushless motor
- Password protection



A	-C	
B D		
	M	
ĮĹ		D
$\left\{ \right\}$	٢٦	

PART NUMBER	TOOL MODEL	DRIVE SIZE		JE (Nm) HIGH	RPM	WEIGHT (Kg)	NOISE LEVEL	DIMENSION A (mm)	DIMENSION B (mm)	DIMENSION C (mm)	DIMENSION D (mm)
31801	B-RAD S 700	0.75″	70	700	21	4.2	85	311	63	70	254
31803	B-RAD S 1400	0.75″	135	1400	9.6	4.3	85	311	63	70	254
31805	B-RAD S 2000	1.0″	200	2000	5.6	4.9	85	321	69	70	254
31807	B-RAD S 4000	1.0″	400	4000	3.0	7.2	85	337	81	81	257
31809	B-RAD S 7000	1.5″	700	7000	1.9	9.8	85	362	95	95	267

Accuracy of +/-5%, Repeatability of +/-2%