

B-RAD XTREME

NEW!



DISPLAY

CASE

Durable, lightweight, shock proof. Designed to protect your RAD investment.



All New Tool with Extreme Battery-Powered Torque!



The all-new B-RAD Xtreme (B-RAD X) raises the bar for torque range capacity with a battery tool, maxing out at an impressive 11,000 ft. lbs./ 15,000 Nm. - making the B-RAD X officially the biggest cordless torque tool on the market. Plus, with 4% accuracy this tool will stand up to the toughest scrutiny. The B-RAD X captures attention with its sleek new white design and rubber handle paired with RAD Torque's patented and world-renowned gearbox technology.

MODELS

- B-RAD X 3000/ 4000-M
- B-RAD X 5000/ 7000-M
- B-RAD X 8000/ 10K-M
- B-RAD X 11K/ 15K-M

ACCESSORIES



SOFT SLING
Great for horizontal or vertical applications and allows the tool to easily pivot between these two orientations.




TOP HANDLE
The top handle is intended for horizontal applications, or applications that can tolerate the extra envelope this adds to the tool.



REAR HANDLE
The rear handle is intended for vertical applications, or for use in conjunction with the sling in horizontal applications to provide a better leverage point over just the handle by itself.

FEATURES

- Brushless DC motor for added durability and accuracy
- Redesigned anti-fatigue trigger switch
- Standard hand-guard for added operator protection
- Two-hand start options to prevent hand injuries
- Battery latch lock to protect batteries from falling
- 4-button interface with high-contrast LED display provides feedback during operation.



IMPERIAL

PART NUMBER	TOOL MODEL	DRIVE SIZE	TORQUE (FT LBS) LOW	TORQUE (FT LBS) HIGH	RPM	WEIGHT (lbs)	DIMENSION A (in)	DIMENSION B (in)	DIMENSION C (in)	DIMENSION D (in)
30983	B-RAD X 3000	1"	250	3000	3.9	17	11.75	3.25	3.5	13.75
30656	B-RAD X 5000	1.5"	500	5000	2.4	23	12.5	3.75	3.75	14.25
30658	B-RAD X 8000	1.5"	740	8000	1.7	30	13.75	4.25	4.25	14.5
30660	B-RAD X 11K*	1.5"	1100	11000	1.2	42	15.25	5	5	14.75

METRIC

PART NUMBER	TOOL MODEL	DRIVE SIZE	TORQUE (Nm) LOW	TORQUE (Nm) HIGH	RPM	WEIGHT (Kg)	DIMENSION A (mm)	DIMENSION B (mm)	DIMENSION C (mm)	DIMENSION D (mm)
30984	B-RAD X 4000-M	1"	340	4000	3.9	7.9	298	83	89	349
30657	B-RAD X 7000-M	1.5"	700	7000	2.4	10.5	318	95	95	362
30659	B-RAD X 10K-M	1.5"	1000	10850	1.7	13.8	349	108	108	369
30661	B-RAD X 15K-M*	1.5"	1500	15000	1.2	19.3	387	127	127	375

Accuracy of +/-4%, Repeatability of +/-2% | *Also available in a 2.5" square drive.