

# E-RAD BLU-S

ELECTRONIC



## Supreme Transducer Technology with High Accuracy

The integrated transducer measures torque output in real time, ensuring the tool stops precisely where it needs to. This feedback loop allows the E-RAD BLU-S to operate accurately regardless of the joint condition and will even allow you to check a previously tightened bolt without applying too much torque.



### CASE

Durable, lightweight, shock proof. Designed to protect your RAD investment.



### SOFT SLING



Great for horizontal or vertical applications and allows the tool to easily pivot between these two orientations.

### FEATURES

- Built-in transducer
- Advanced data logging and tool management features
- Password protection on three user levels: basic, intermediate, and advanced
- Operator identification ensures traceability of each torque sequence performed
- Capable of torque and angle bolting sequence
- LED indicator lights (pass/fail)
- Extremely low noise level at only 75dB


### TOUCH CONTROL CASE

- Easy to use interface
- Pre-sets for torque and angle adjustments
- Quick error-free torque and angle adjustments
- Complete recalibrations
- Data logging with export to laptop



### RAD SMART SOCKETS™

RAD SMART SOCKETS™ can connect to the E-RAD BLU tool via **Bluetooth®** technology. This combination allows you to automatically calibrate your E-RAD BLU to any joint!



### IMPERIAL

PART NUMBER	TOOL MODEL	DRIVE SIZE	TORQUE (ft. lbs.) LOW	TORQUE (ft. lbs.) HIGH	RPM 120V	RPM 230V	WEIGHT (lbs.)	DIMENSION A	DIMENSION B	DIMENSION C	DIMENSION D
30079	E-RAD BLU-S 700	0.75"	100	700	15	30	13	14.96"	2.84"	3.03"	10.65"
28836	E-RAD BLU-S 2500 COMP	1.0"	250	2500	5	10	19	16.21"	3.41"	3.03"	10.65"
31190	E-RAD BLU-S 3000	1.0"	500	3000	5	10	24.5	17.76"	3.73"	3.48"	11.29"
31191	E-RAD BLU-S 6000	1.5"	1000	6000	2.1	4.5	30	17.71"	4.35"	3.48"	11.29"
31192	E-RAD BLU-S 7500	1.5"	1500	8000	1.5	3	34	18.53"	4.48"	3.48"	11.29"
29314	E-RAD BLU-S 11K*	1.5"	3000	11000	1.5	2.3	44	19.81"	5.21"	3.48"	11.29"

### METRIC

PART NUMBER	TOOL MODEL	DRIVE SIZE	TORQUE (Nm) LOW	TORQUE (Nm) HIGH	RPM 120V	RPM 230V	WEIGHT (Kg)	DIMENSION A (mm)	DIMENSION B (mm)	DIMENSION C (mm)	DIMENSION D (mm)
26937	E-RAD BLU-S 950-M	0.75"	135	950	15	30	5.9	380	72	77	270.5
26938	E-RAD BLU-S 3400-M COMP	1.0"	340	3400	5	10	8.6	412	87	77	270.5
22759	E-RAD BLU-S 4000-M	1.0"	675	4000	5	10	11.1	451	95	88	287
25282	E-RAD BLU-S 8000-M	1.5"	1350	8100	2.1	4.5	13.6	450	110.5	88	287
26939	E-RAD BLU-S 10K-M	1.5"	2000	10000	1.5	3	15.4	471	114	88	287
29315	E-RAD BLU-S 15K-M*	1.5"	4050	15000	1.5	2.3	20	503	132	88	287

Bluetooth® is a registered trademark of Bluetooth SIG, Inc. and any use of such marks by New World Technologies Inc. is under license. Other trademarks and trade names are those of their respective owners.

Accuracy of +/- 2.8%, Repeatability of +/- 2% | \*Also available in a 2.5" square drive.