

E-RAD BLU

ELECTRONIC



Ability to use different handles with controller case

E-RAD BLU precision torque wrench tools are designed to provide a high degree of accuracy (+/- 2.8%) and repeatability (+/- 2%). Using a patented gearbox design and the precision of an electric AC Servo motor, these tools deliver smooth continuous torque. Best of all, it's the most affordable system on the market.

FEATURES

- Advanced data logging and tool management features
- Military grade single cable and connector system
- Available in a 90-degree gearbox
- LED indicator lights (pass/fail)
- Push-button select torque
- Lightweight and ergonomic pistol grip


TOUCH CONTROL CASE

- Easy to use interface
- Pre-sets for torque and angle adjustments
- Quick error-free torque and angle adjustments
- Complete recalibrations
- Data logging with export to laptop



RAD SMART SOCKETS™

RAD SMART SOCKETS™ can connect to the E-RAD BLU tool via **Bluetooth®** technology. This combination allows you to automatically calibrate your E-RAD BLU to any joint!



IMPERIAL

PART NUMBER	TOOL MODEL	DRIVE SIZE	TORQUE (ft. lbs.) LOW	TORQUE (ft. lbs.) HIGH	RPM 120V	RPM 230V	WEIGHT (lbs.)	DIMENSION A	DIMENSION B	DIMENSION C	DIMENSION D
21980	E-RAD BLU 700	0.75"	100	700	15	30	12	13.25"	2.5"	3.0"	10.65"
24161	E-RAD BLU 1500	1.0"	200	1500	8	16	13	13.28"	2.7"	3.0"	10.65"
21981	E-RAD BLU 2500 COMP	1.0"	250	2500	4.9	10	18	14.8"	3.0"	3.0"	10.65"
24221	E-RAD BLU 2500 COMP-90-Degree	1.0"	250	2500	6	12	18	9.65"	3.0"	3.1"	11.83"
21982	E-RAD BLU 3000	1.0"	500	3000	4.1	8.5	23.5	16.75"	3.4"	3.5"	11.29"
21983	E-RAD BLU 6000	1.5"	1000	6000	2.1	4.5	29	16.5"	4.0"	3.5"	11.29"
21984	E-RAD BLU 7500	1.5"	1500	7500	1.5	3	33	17.0"	4.25"	4.25"	11.29"
24234	E-RAD BLU 11K*	1.5"	3000	11000	1.2	2.3	43	18.3"	5.0"	5.0"	11.29"

METRIC

PART NUMBER	TOOL MODEL	DRIVE SIZE	TORQUE (Nm) LOW	TORQUE (Nm) HIGH	RPM 120V	RPM 230V	WEIGHT (Kg)	DIMENSION A (mm)	DIMENSION B (mm)	DIMENSION C (mm)	DIMENSION D (mm)
21985	E-RAD BLU 950-M	0.75"	135	950	15	30	5.5	340	65	78	275
24162	E-RAD BLU 2000-M	1.0"	270	2000	8	16	5.9	337	69	78	275
21986	E-RAD BLU 3400-M COMP	1.0"	340	3400	4.9	10	7.6	380	76	78	275
22434	E-RAD BLU 3400-M COMP-90-Degree	1.0"	340	3400	6	12	8.3	210	76	78	300
21987	E-RAD BLU 4000-M	1.0"	675	4000	4.1	8.5	11	430	86	88	287
21988	E-RAD BLU 8000-M	1.5"	1350	8000	2.1	4.5	13.5	419	100	100	287
21989	E-RAD BLU 10K-M	1.5"	2000	10000	1.5	3	15	432	105	105	287
24224	E-RAD BLU 15K-M*	1.5"	4000	15000	1.2	2.3	20	465	127	127	287

Accuracy of +/-2.8%, Repeatability of +/-2% | *Also available in a 2.5" square drive.



90 DEGREE*

OFFSET*

*Only available on certain models.

SHOWN WITH OPTIONAL MOUNTING ACCESSORY

CASE

Durable, lightweight, shock proof. Designed to protect your RAD investment.



Bluetooth® is a registered trademark of Bluetooth SIG, Inc. and any use of such marks by New World Technologies Inc. is under license. Other trademarks and trade names are those of their respective owners.