

V-RAD SELECT

Quick adjust torque with equal power in forward and reverse



V-RAD Select electric torque wrench is used for the installation or removal of heavy-duty fasteners where accuracy, power, and safety are required. Quick adjust torque settings. Equal power in forward and reverse.

FEATURES

- Torque ranges up to 3,000 ft. lbs./ 4,000 Nm
- Digital torque settings to increase and decrease the value by 10 ft. lbs./ 10 Nm
- Available in both 120V or 230V

CASE

Durable, lightweight, shock proof.
Designed to protect your RAD investment.



IMPERIAL

PART NUMBER	TOOL MODEL	DRIVE SIZE	TORQUE (ft. lbs.)		RPM	WEIGHT (lbs.)	DIMENSION A	DIMENSION B	DIMENSION C	DIMENSION D
			LOW	HIGH						
25628	V-RAD SELECT 1000	0.75"	100	1000	8.8	8.6	12"	2.5"	2.9"	8"
25629	V-RAD SELECT 1500	1.0"	150	1500	5.7	9.6	12.25"	2.7"	2.9"	8"
25631	V-RAD SELECT 3000	1.0"	300	3000	2.7	13.7	13.5"	3.1"	3.1"	8"

METRIC

PART NUMBER	TOOL MODEL	DRIVE SIZE	TORQUE (Nm)		RPM	WEIGHT (Kg)	DIMENSION A (mm)	DIMENSION B (mm)	DIMENSION C (mm)	DIMENSION D (mm)
			LOW	HIGH						
25633	V-RAD SELECT 1400-M	0.75"	140	1400	8.8	3.9	305	64	74	203
25634	V-RAD SELECT 2000-M	1.0"	200	2000	5.7	5.9	311	69	74	203
25636	V-RAD SELECT 4000-M	1.0"	400	4000	2.7	6.2	343	79	79	203

Accuracy of +/-5%, Repeatability of +/-2%

