

B-RAD® XTREME



Screen Display



B-RAD X Series



CASE
Durable, lightweight and shock proof. Designed to protect your RAD investment.

More Torque Ranges. More Speed. More Possibilities.

The award-winning B-RAD Xtreme Series has evolved into the most comprehensive cordless industrial torque wrench lineup. With 7 torque ranges, 9 configurations and a torque capacity from 50 to 11,000 ft-lb (70–15,000 Nm), there's a B-RAD Xtreme built for every industrial bolting application.


Three new lower torque models expand the series, delivering up to 55% faster torque cycles than our popular B-RAD Select Series, helping operators complete more bolting jobs in less time without compromising accuracy or reliability.

The lineup also includes Shaft Retention (B-RAD X-C) models, designed for mining haul truck wheels and other equipment with bolts located between rim walls or behind obstructions.

Built around RAD Torque's patented gearbox technology, a high-performance brushless DC motor and advanced fastening electronics, every B-RAD Xtreme delivers exceptional battery efficiency, repeatable accuracy and the rugged durability professionals rely on every day.

Why B-RAD Xtreme?

- Available in 7 torque ranges from 50–11,000 ft-lb (70–15,000 Nm)
- Torque + Angle functionality for advanced bolting control
- Gearboxes optimized for faster torque cycles
- Brushless DC motor
- High-capacity lithium-ion battery system
- Intuitive 4-button interface with high-contrast LED display
- Redesigned ergonomic controls
- NFPA 70 NEC Certified: Class I, Division 2
- Award-winning platform recognized by the Edison Awards and Pro Tool Innovation Awards



IMPERIAL

	Part Number	Tool Model	Drive Size	Torque (ft-lb)		RPM	Accuracy	Weight (lbs.)	Dimension A (in)	Dimension B (in)	Dimension C (in)	Dimension D (in)
				Low	High							
NEW	32576	B-RAD X 500	.75"	50	500	27.6	3.5%*	11.1	9.25	2.48	3.62	13.87
NEW	32651	B-RAD X 1000	.75"	100	1000	14.5	3.5%*	12.3	10.63	2.48	3.62	13.87
NEW	32653	B-RAD X 1500	1"	150	1500	9.3	3.5%*	13.1	10.44	2.7	3.62	14.06
	30983	B-RAD X 3000	1"	250	3000	3.9	4%	17	12	3.18	3.62	13.88
NEW	34435	B-RAD X 3000-C	1"	250	3000	3.9	4%	17	12	3.18	3.62	13.88
	30656	B-RAD X 5000	1.5"	500	5000	2.4	4%	23	12.31	3.74	3.75	14.13
NEW	34437	B-RAD X 5000-C	1.5"	500	5000	2.4	4%	23	12.75	3.74	3.75	14.13
	30658	B-RAD X 8000	1.5"	740	8000	1.7	4%	30	13.88	4.25	4.25	14.38
	30660	B-RAD X 11K*	1.5"	1100	11000	1.2	4%	42	15.25	5	5	14.91

METRIC

	Part Number	Tool Model	Drive Size	Torque (Nm)		RPM	Accuracy	Weight (kg)	Dimension A (mm)	Dimension B (mm)	Dimension C (mm)	Dimension D (mm)
				Low	High							
NEW	32577	B-RAD X 700-M	.75"	70	700	27.6	3.5%*	5	235	63	93	353
NEW	32652	B-RAD X 1400-M	.75"	140	1400	14.5	3.5%*	5.6	270	63	93	353
NEW	32654	B-RAD X 2000-M	1"	200	2000	9.3	3.5%*	6	266	69	93	358
	30984	B-RAD X 4000-M	1"	340	4000	3.9	4%	7.9	305	81	93	353
NEW	34436	B-RAD X 4000-M-C	1"	400	4000	3.9	4%	7.9	305	81	93	353
	30657	B-RAD X 7000-M	1.5"	700	7000	2.4	4%	10.5	313	95	95	359
NEW	34438	B-RAD X 7000-M-C	1.5"	700	7000	2.4	4%	10.5	313	95	95	359
	30659	B-RAD X 10K-M	1.5"	1000	10850	1.7	4%	13.8	353	108	108	366
	30661	B-RAD X 15K-M*	1.5"	1500	15000	1.2	4%	19.3	388	127	127	379

* ±3.5% accuracy full scale. All other models have ±4% accuracy to target | Repeatability of ±2% | *Also available in a 2.5" square drive