

E-RAD® BLU-S



CASE
Durable, lightweight and shock proof. Designed to protect your RAD investment.

Supreme Transducer Technology with High Accuracy




The integrated transducer measures torque output in real time, ensuring the tool stops precisely where it needs to. This feedback loop allows the E-RAD BLU-S to operate accurately regardless of the joint condition and will even allow you to check a previously tightened bolt without applying too much torque.

FEATURES

- Built-in transducer
- Advanced data logging and tool management features
- Password protection on three user levels: basic, intermediate, and advanced
- Operator identification ensures traceability of each torque sequence performed
- Capable of torque and angle bolting sequence
- LED indicator lights (pass/fail)
- Extremely low noise level at only 75dB

TOUCH CONTROL CASE

- Easy to use interface
- Pre-sets for torque and angle adjustments
- Quick error-free torque and angle adjustments
- Complete recalibrations
- Data logging with export to laptop



IMPERIAL

Part Number	Tool Model	Drive Size	Torque (ft-lb) Low High	RPM 120V	RPM 230V	Weight (lbs.)	Dimension A (in)	Dimension B (in)	Dimension C (in)	Dimension D (in)
30079	E-RAD BLU-S 700	.75"	100 700	15	30.5	12.2	13.4	2.5	3	10.75
28836	E-RAD BLU-S 2500 COMP	1"	250 2500	4.9	10.3	17.1	14.5	3	3	10.75
31190	E-RAD BLU-S 3000	1"	500 3000	4.9	10.3	20.8	14.5	3	3	10.75
31191	E-RAD BLU-S 6000	1.5"	1000 6000	2.1	4	32.3	16.3	4	4	11.5
31192	E-RAD BLU-S 7500	1.5"	1500 7500	1.5	3	36.5	18.5	4.5	4.5	11.5
29314	E-RAD BLU-S 11K*	1.5"	3000 11000	1.5	2.3	44	19.8	5.2	5.2	11.5

METRIC

Part Number	Tool Model	Drive Size	Torque (Nm) Low High	RPM 120V	RPM 230V	Weight (Kg)	Dimension A (mm)	Dimension B (mm)	Dimension C (mm)	Dimension D (mm)
26937	E-RAD BLU-S 950-M	.75"	140 950	15	30.5	5.5	339	64	76	273
26938	E-RAD BLU-S 3400-M COMP	1"	340 3400	4.9	10.3	7.8	368	76	76	273
22759	E-RAD BLU-S 4000-M	1"	700 4000	4.9	10.3	9.5	368	76	76	273
25282	E-RAD BLU-S 8000-M	1.5"	1400 8000	2.1	4	14.7	414	102	102	292
26939	E-RAD BLU-S 10K-M	1.5"	2000 10000	1.5	3	16.6	471	114	114	292
29315	E-RAD BLU-S 15K-M*	1.5"	4000 15000	1.5	2.3	20	503	132	132	292

±2.8% accuracy to target | Repeatability of ±2% | *Also available in a 2.5" square drive