

RAD HIGH SPEED

Extreme-Duty Torque Wrenches with High RPM Productivity



Looking for high RPM productivity? RAD High Speed torque wrenches incorporate a precision-engineered, high-speed gearbox designed for faster run down and quick reaction point positioning on time sensitive bolting applications.


The two-speed models feature a unique fully automatic gearbox design, eliminating the time-consuming switch between high and low speed gear.

FEATURES

- The ultimate in power-to-weight ratio
- Wide torque range to suit multiple applications
- Unmatched reliability delivered by one of the most advanced engineered gear boxes on the market
- Controlled torque - accuracy of $\pm 5\%$ and repeatability of $\pm 2\%$

FRL UNIT

- Low weight tool holder made from high-density polypropylene
- Includes pressure gauge, filter, regulator and oiler



IMPERIAL

Part Number	Tool Model	Drive Size	Torque (ft-lb)		RPM	Weight (lbs.)	Noise Level	Dimension A (in)	Dimension B (in)	Dimension C (in)	Dimension D (in)
			Low	High							
10644	RAD 10GX-2	.75"	350	1000	72	9.9	80 db	10.2	2.5	2.8	9
17068	RAD 15DX-2	1"	500	1500	56	10.6	80 db	10.2	2.7	2.8	9
19773	RAD 25GX-2	1"	700	2500	52	16.5	80 db	12.1	3.1	3.3	9.5
24950	RAD 30DX-2	1"	1000	3000	51	16.1	80 db	12.2	3.2	2.8	9.5

METRIC

Part Number	Tool Model	Drive Size	Torque (Nm)		RPM	Weight (Kg)	Noise Level	Dimension A (mm)	Dimension B (mm)	Dimension C (mm)	Dimension D (mm)
			Low	High							
19774	RAD 14GX-2-M	.75"	475	1400	72	4.5	80 db	259	63	70	228
19775	RAD 20DX-2-M	1"	700	2000	56	4.8	80 db	259	69	70	228
19776	RAD 34GX-2-M	1"	950	3400	52	7.5	80 db	308	77	84	242
24952	RAD 40DX-2-M	1"	1400	4000	51	7.3	80 db	309	81	84	242

$\pm 5\%$ accuracy to target | Repeatability of $\pm 2\%$